

AUCMA CO.,LTD.

315 Qianwangang Road,, Economic & Technological Development Zone, QINGDAO, CHINA 266061

PRODUCT SPECIFICATION

Model	YC-1006
Photo	
Capacity (gross)	1006L
Capacity (net)	976L
Type	Vertical
Temperature range	2~8°C
Increment of adjustment	0.1°C
Power supply	230V~/50Hz
Power	520+15W
Power consumption, kWh/24h	5.82
Climate class (N, SN, T, ST or 4, 4+, 5)	4
Noise level dB	58
Automatic/ manual defrost	Automatic
Equipped with PT100 or NTC probe	NTC
Interior dimension	1100*585*1740mm
Exterior dimension	1200*710*2020mm
Package dimension	1270*780*2180mm
Net/gross weight	169/191Kg
Insulation layer	PU
Insulation thickness	50mm
Internal material	Prepainted aluminum plate
Door frame material	Aluminium alloy
Compressor	Hermetic
Name of the Compressor	EMTE2134U EMBRACO
Refrigerant	R290
Evaporator type	Fin type

Condenser type	Skin tube
External material	Painted steel
Forced air cooling system	yes
Air channel design have built-in condenser	Professional air channel
Electrical heating vertical beam prevents condensation	yes
Transparent holow tempered galvanized reflex glass door	yes
Condensate drain on condensate	yes
Magnetic door seal	yes
Inner and outer double door design	n/a
Door reversible	n/a
Grate shelves	12
Adjustable shelves	yes
Max. Shelf load	15Kg
Wheel	yes
Wheel with locking function	Foot screws
Adjustable legs	2
Lock with key	yes
Thermometer hole design	n/a
Internal LED light	yes
Micro-computer features	
Temperature controller	Electronic temperature controller
Temperature display (LED display) or LCD display	LED
LCD display screen	n/a
USB connection	n/a
Approx.72 hrs. of battery backup for alarms and temperature alarms and temperature display in the event of power cut	72 hours of power failure alarm, display the actual temperature in the box
Prepared for GSM alarm module	n/a
Prepared for connection of 2 additional probes	Optional
Auto cycle in case of probe failure	yes
Ambient temperature display	yes
Direct download of logged data on USB memory stick	n/a
Direct upload o new sotware via USB memory stick	n/a
Keyboard lock	yes
Battery level indication	Low voltage alarm
Alarm features	
high low temperature alarm - Buzzer alarm	standard
high low temperature alarm - Light alarm	standard
high low temperature alarm - Remote alarm	Normally open contact
sensor malfuction alarm - Buzzer alarm	standard
sensor malfuction alarm- Light alarm	standard

sensor malfunction alarm - Remote alarm	standard
under voltage alarm - Buzzer alarm	standard
under voltage alarm - Light alarm	n/a
under voltage alarm - Remote alarm	standard
open the door alarm - Buzzer alarm	standard
open the door alarm - Light alarm	standard
open the door alarm - Remote alarm	standard
low battery alarm - Buzzer	standard
low battery alarm - Light alarm	standard
low battery alarm -Remote alarm	standard
power failure alarm - Buzzer alarm	standard
power failure alarm - Light alarm	standard
power failure alarm - Remote alarm	standard
probe failure alarm	standard