

AUCMA CO.,LTD.

315 Qianwangang Road,, Economic & Technological Development Zone, QINGDAO, CHINA 266061

PRODUCT SPECIFICATION

Model	YCD-288A	
	Refrigerator part	Freezer part
Picture		
Capacity (gross)	188	100
Capacity (net)	182	97
Temperature range (°C)	2-8°C	-20 ~ -40°C
Increment of adjustment	0.1°C	1°C
Temperature controller	electronic temperature controller	electronic temperature controller
Temperature display	LED	LED
Type/outer door	foaming door with toughened glass	foaming door
Climate type	4	4
Power supply(V/Hz)	230/50	230/50
Power(W)	430	
Power consumption (kWh/24h)	4,8 kWh/24h	
Noise level dB	50	
Automatic/manual defrost	/	manual
NO Frost	NO Frost	/
Equipped with PT100 probe or NTC	The NTC sensor	
Internal dimensions(W*D*H)	588×552×630	511×491×415
External dimensions(W*D*H)	737×780×1860	
Packing dimensions(W*D*H)	815×850×2070	
Net/gross weight	146/175	
Exterior cabinet	cold-rolled steel plate,	
Interior cabinet	stainless steel	
Insulation material	PU	
Insulation thickness	55	100
Forced air cooling system	yes	no

Refrigerant type	HC	HC
Refrigerant	R290	R290
Evaporator type	roll bond	skin tube
Condensor type	built-in type	external coil
Qty of Compressors	1	1
Compressor (Brand)	EM2X3113U	EMTE2134U
Shelves & Sliding Racks	stainless shelf+drawer	basket&drawer
Possibility to close the refrigerating chamber independently	yes	no
Outer door lock	1	1
Magnetic door seal	yes	yes
Heating free pressure-balanceed valve or heated gasket	/	yes
Thermometr hole design	no	yes
Internal LED light	Yes	no
Wheels	4	
Shelf	3	/
Drawer	1	2
Alarm features		
High/low Temperature- Buzzer Alarm	yes	yes
High/low Temperature- Light Alarm	yes	yes
High/low Temperature – Remote Alarm	yes	yes
Power failure alarm-Buzzer Alarm	yes	yes
Power failure alarm- Light Alarm	yes	yes
Power failure alarm - Remote Alarm	yes	yes
Sensor error alarm- Buzzer Alarm	yes	yes
Sensor error alarm- Light Alarm	yes	yes
Sensor error alarm- Remote Alarm	yes	yes
Low battery alarm- Buzzer Alarm	yes	yes
Low battery alarm - Light Alarm	yes	yes
Low battery alarm - Remote Alarm	yes	yes
Door open alarm - Buzzer Alarm	yes	yes
Door open alarm -Light Alarm	yes	yes
Door open alarm - Buzzer Alarm	yes	yes
Micro-computer features		
USB port	yes	
Temperature Recorder	Yes (More than one month of data stored)	
Approx. 72 hrs. of battery back-up for alarms and temperature alarms and temperature display in the event of power cut	yes	yes
Prepared for GSM alarm module	no	
Ambient temperature display	yes	
Direct download of logged data on USB memory stick	yes	
Password protected eg. 3-level	yes	
Battery level indication	no	
RS 485/ RS 232 Interface	no	